

RECIPROCATING SAW BI-METAL BLADES



| Model Numbers | Length | Teeth Per Inch (TPI) | Recommended for cutting: |
|---------------|--------|----------------------|--------------------------------------|
| RAWRB606HD | 6" | 6 | Wood with nails, General Roughing in |
| RAWRB906HD | 9" | 6 | Wood with nails, General Roughing in |
| RAWRB610 | 6" | 10 | Wood, Plastic & Steel |
| RAWRB910 | 9" | 10 | Wood, Plastic & Steel |
| RAWRB614 | 6" | 14 | Metal 3/16" thru 1/4" |
| RAWRB614HD | 6" | 14 | Metal 3/16" thru 1/4" |
| RAWRB814 | 8" | 14 | Metal 3/16" thru 1/4" |
| RAWRB914HD | 9" | 14 | Metal 3/16" thru 1/4" |
| RAWRB618 | 6" | 18 | Metal 1/8" thru 3/16" |
| RAWRB818 | 8" | 18 | Metal 1/8" thru 3/16" |
| RAWRB918HD | 9" | 18 | Metal 1/8" thru 3/16" |
| RAWRB624 | 6" | 24 | Metal thinner than 1/8" |

Features & Benefits

- 8% Cobalt edge offers more wear resistance to last longer
- Matrix II cutting profile resists stripping and cuts faster
- Available in a wide variety of lengths and thicknesses
- Fits all popular corded and cordless reciprocating saws

Caution: blades are very sharp
Always use safety goggles and hand protection when cutting

Applications

- Most machinable metals
- Wood and nail-embedded wood
- Composites
- Rubber
- Plastic, PVC, & CPVC
- Plaster
- Numerous other common building materials

| 6 TPI | 10 TPI | 14 TPI | 18 TPI | 24 TPI |
|---|--------|--------|--------|--------|
| WOOD | | | | |
| PLASTER (w/ mesh and lath) | | | | |
| GENERAL DEMOLITION (wood and nail embedded wood) | | | | |
| PLASTICS AND COMPOSITES | | | | |
| THICK METAL - 1/8" to 1/2" thick | | | | |
| MEDIUM METAL - 3/32" to 5/16" thick | | | | |
| THIN METAL - 1/8" or less thick | | | | |



Made in U.S.A.

Warranty

1-year against manufacturer's defects.